

















Polyurethane Pigment Color Chart

Professional Grade Colorants for Superior Finish Quality
Compatible with most polyurethane resin systems

Updated: September 2025 | Version 2.0

Application Guidelines

Dosage Rate: 0.5% to 5% by weight for optimal color development
Mixing: Add pigment slowly while stirring to ensure even dispersion
Compatibility: Test small batches before full production runs

| | | | |
|---|---|---|---|
|  <div>Red 100 R100</div> |  <div>Red 120 R120</div> |  <div>Orange 220 O220</div> |  <div>Yellow 315 Y315</div> |
|  <div>Green 430 G430</div> |  <div>Green 420 G420</div> |  <div>Light Blue 530 LB530</div> |  <div>Dark Blue 500 DB500</div> |
|  <div>Light Brown LB745</div> |  <div>Mid Brown 745 MB745</div> |  <div>Dark Brown 700 DB700</div> |  <div>Grey 900 G900</div> |
|  <div>Black 615 B615</div> |  <div>White 810 W810</div> | | |

Technical Specifications

Storage Conditions

Store in cool, dry place away from direct sunlight. Temperature: 5°C to 25°C. Shelf life: 24 months when properly stored.

Safety Information

Use in well-ventilated area. Wear appropriate PPE. Consult Safety Data Sheet before use. Keep away from children.

Important Notice: Colors shown are representative only and may vary due to printing limitations, monitor settings, and substrate type. Always test color samples before final application.
Custom colors and tints available by blending pigments. Consult technical support for special requirements.

Dalchem Technical Support
Email: sales@dalchem.com.au | Web: www.dalchem.com.au
Phone: 03 95537040